MARSDEN

PB-SS Stainless Steel Weigh Beams



- Stainless Steel Weigh Beams
- IP68 Waterproof Structure
- Built in carry handles and wheels

- 4m of loadcell cable included
- · Adjustable levelling feet
- · Suitable for all warehouse and factory areas

Marsden Weigh Beams:

Indicators for the PB-SS









I-100SS Indicator

- Stainless ateel housing
- IP65 Protection
- Functions include Zero, Tare/Pre-set Tare, Counting and Accumulation

The Marsden I-100SS is our best-selling stainless steel indicator for industrial weighing scales.

It's hard wearing, practical and affordable, and has a number of functions to make weighing easier: Tare, a basic Counting function, an Accumulation mode, to find the total of several weight readings.

A Trade Approved version of this indicator is available.

I-200 Indicator

- IP67 splashproof stainless steel indicator
- Functions include Zero, and Tare/Pre-set Tare
- Bright red LED display for easy readings

The Marsden I-200 is an IP67-certified industrial weighing indicator with a bright red digital display.

This easy to use, hard wearing stainless steel indicator is ideal for use in food factories, fish markets and other harsh environments requiring hosing down of equipment to keep clean and hygeinic.

I-400SS Indicator

- IP68-certified waterproof stainless steel indicator
- 50mm high LCD display
- · Suitable for liquid filling
- Auto power-off function to save battery

The Marsden I-400SS is a stainless steel, IP68-certified waterproof industrial weighing indicator.

The I-400SS is our most hardy industrial indicator and suitable for wet, humid and dusty environments. Functions include Tare, Gross and Zero and it is also suitable for liquid filling applications.

JIK Indicator

- IP67 splashproof, stainless steel indicator
- RS-232 interface board
- Large backlight display
- 1/6,000 display resolution for accurate weighing

The Jadever JIK is an intelligent IP67 indicator witha wide range of features and data transfer options.

You can also transfer weight/ count data directly from the indicator to a computer. Other key features include Counting, Tare, Pre-set Tare, second scale input and optional remote display.

A Trade Approved version of this indicator is available.

IP Rating:	IP65
Power:	Mains/Battery
Display Resolution:	1/30,000 (Non- Approved) 1/3,000 (Approved)
Functions:	Counting, Zero, Tare

IP Rating:	IP67
Power:	Mains/Battery
Display Resolution:	1/30,000 (Non- Approved)
Functions:	Zero, Tare, Pre-set Tare

IP Rating:	IP68
Power:	Mains/Battery
Display Resolution:	1/30,000 (Non- Approved)
Functions:	Liquid Filling, Tare, Zero, Gross

IP Rating:	IP67
Power:	Mains/Battery
Display Resolution:	1/60,000 (Non- Approved) 1/6,000 (Approved)
Functions:	Unit Switchable, Liquid Filling, Data Transfer, Counting, Zero, Tare, Pre-set Tare